CustomLED 2011-2013 Ducati Diavel Blinker Genie

Illustrated Installation Instructions

Download hi-resolution instructions at https://www.customled.com/BGDiavel

This 100% plug-and-play kit allows for run and turn operation of the OEM pilot light assemblies 😊







 Push intake grill to the side and remove the 10mm bolt securing radiator stay to side cover.



5) Repeat procedure on left side of motorcycle.





7) Rout long legs of blinker genie harness from behind steering neck area down to turn signal connectors on each side of motorcycle. Route wires inside of frame. See next image for more details.

(continued on other side)



White wire on LEFT side, Green wire on RIGHT. To assist with routing, snake mechanics wire (or similar) from behind radiator support bolt up to frame area behind neck, and pull harness down.

9) Tuck other connector behind radiator shroud and zip tie cables together. Repeat on opposite side.





8) Connect Blinker Genie legs to mating connectors. Position connector from lamp into in retention slot.



10) Locate the headlamp 2-wire connector attached to neck. Slide up and off of mounting tab on neck. Disconnect connector.

11) Connect Blinker Genie connectors to their mating connectors on the headlamp wires.



12) Reattach one headlamp connector to mounting tab on frame. Tuck other connector and B.G. body inside of frame

13) Zip-Tie wires as necessary to prevent interference with steering movement

14) Reinstall the left and right side covers and mounting hardware.

15) Enjoy! 😊

Thank you for choosing Custom LED, and supporting USA manufacturing. Please help spread the word! You can share Video of this product in action on **YouTube**, and share your pre and post-install pictures on **Instagram**. Be sure to tag us **@Custom_LED_LLC** in the pictures so they will appear on our website Instagram feed!